



1 CORE



3 CORE



Symbol	A	B	C	Insulation Range	
				Min	Max
G	374	513	95.5	21.0	23.0
J	411	549		23.0	25.0
N	374	513		25.5	28.0
JA	385	524	108	29.0	31.0
JAB	418	582		31.0	32.5
JB	381	546		33.5	35.0
KA	418	578		36.5	38.0
KB	385	546		39.5	41.0
PA				41.5	43.0
PW	411	572	120	44.5	47.5
Q	385	546		51.5	53.0

NOTE

1. 일반공차 : ±5%

NO	DESCRIPTION	MATERIAL	Q'TY	DWG. NO	REMARK
7	Copper Braid	Copper Alloy			
6	Trifurcating Groove Bracket	EPDM Rubber			
5	Stress Cone	EPDM Rubber			
4	Module(Skirt)	EPDM Rubber			
3	Rain Cap	EPDM Rubber			
2	Terminal Lug	Copper Alloy			

이 자료는 평일산업주식회사의
 산업재산권이므로, 무단복사 또는
 타인에게 유출할 수 없습니다.
 PYUNG-IL INDUSTRIAL CO.,LTD.
 PROPRIETARY RIGHTS

DATE	RVSD BY	REVISD CONTENTS	UNIT	mm		TITLE	35MT FOR 종단접속제				
			SCALE	1:1(A3)		DSGN BY	CHKD BY	APPD BY	DWG NO	PIS08000	REV NO
			PROJ.	3RD ANGLE	B.Y. HAN			REF NO	-	SHT NO	/
			DATE	2010.07.16							